



PRINT



SAVE AS PDF

MAG 1[®] CONTINUOUSLY VARIABLE TRANSMISSION FLUID

PASSENGER CAR TRANSMISSION PRODUCTS AUTOMATIC TRANSMISSION PRODUCTS



MAG 1 CVT Fluid is specially formulated with a unique combination of full synthetic base stocks and an advanced additive technology designed for the specific demands of CVTs. This premium-quality product is recommended for use in most belt or chain-driven CVTs. It is not a replacement for ATF.

PROTECTION FOR TODAY'S AUTOMATIC TRANSMISSION DESIGNS

Automotive transmissions have evolved dramatically, requiring highly specialized fluids for unique applications. One brand has evolved right alongside – MAG 1[®]. Only the most advanced transmission fluids meet the difficult challenges of effectively balancing performance, strength and durability.

Featuring MAG 1[®] with FMX[®] Technology – Friction Management for Xtreme protection™. MAG 1 is designed to provide unsurpassed protection.

PERFORMANCE

- Delivers superior friction stability to maintain smooth, consistent shifting and prevent shudder.

STRENGTH

- Provides a strong oil film to prevent metal-to-metal contact between rotating parts to prevent wear.

DURABILITY

- Resists thickening due to high operating temperatures.

APPLICATIONS MAY INCLUDE:

- Audi/VW (TL 521 80; G 052 180, TL 521 16; G 052 516)
- BMW Mini Cooper (EZL 779)
- Dodge/Jeep/Chrysler (NS-2 / CVTF+4)
- Honda (HMMF, HCF2)
- Hyundai/Kia (CVTF-J1)
- Mazda (JWS 3320)
- Mercedes Benz (236.20)
- Mitsubishi (CVTF-J1, CVTF-J4)
- Nissan (NS-1, NS-2, NS-3)
- Punch CVT
- Subaru (iCVT, iCVT FG, eCVT, Lineartronic CVT and CVT II)

- Suzuki (CVTF TC, NS-2, CVT Green 1)
- Toyota (CVTF TC, CVTF FE)

INDUSTRY/OEM SPECIFICATIONS

Audi/VW (TL 52180; G 052 180; G 052 516)	Suitable for Use
BMW 8322 0 136 376/8322 0 429 154(EZL799/EZL 799A)	Suitable for Use
Daihatsu Amix CVTF-DC, Daihatsu AMIX CVTF-DFE	Suitable for Use
Dodge / Jeep (NS-2 / CVTF+4/Mopar CVT 4)	Suitable for Use
Ford CFT30/WSS-M2C933-A /Motorcraft XT-7-QCFT	Suitable for Use
GM/Saturn (DEX-CVT, CVTF I-Green2)	Suitable for Use
Honda (HMMF, HCF-2)	Suitable for Use
Hyundai/KiaCVTF (SP-CVT 1)	Suitable for Use
Mazda CVTF 3320	Suitable for Use
Mercedes Benz (236.20)	Suitable for Use
Mercedes Benz CVT28/MB-Approval 236.20	Suitable for Use
Mini Cooper (EZL 799/ EZL 799A/ZF CVT V1)	Suitable for Use
Mitsubishi (CVTF-J1)	Suitable for Use
Mitsubishi DiaQueen (CVTF-J1, CVTF-J4)	Suitable for Use
Nissan (NS-1, NS-2, NS-3)	Suitable for Use
Punch EZL 799/EZL 799A	Suitable for Use
Renault ELFMATIC	Suitable for Use
Shell Green 1V	Suitable for Use
Subaru (NS-2 / Lineartronic CVTF, i-CVTF,K0425Y0710) e-CVTF	Suitable for Use
Suzuki (TC / NS-2 / CVTF Green 1, CVTF Green 2, CVTF 3320)	Suitable for Use
Toyota (TC, FE)	Suitable for Use

TYPICAL PROPERTIES

Brookfield Viscosity at -40°C, cP	ASTM D2983	12,300
Color	ASTM D1500	Amber
Flash Point °C	ASTM D92	199
Flash Point °F	ASTM D92	390
Gravity, °API	ASTM D287	34.23
Pour Point °C (°F)	ASTM D5950	-51°C (-60°F)
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8538
Viscosity @ 100°C cSt	ASTM D445	7.21
Viscosity @ 40°C cSt	ASTM D445	33.8
Viscosity Index	ASTM D2270	185

CONTAINER/BULK AVAILABILITY

6/1 Quart	Product Number - 63318
-----------	------------------------

Available in Bulk

Information accurate as of May 5, 2025